



The BT1100 is equipped with our latest operating system and a colored LCD to maximize usability and flexibility. The screen is also able to display cranking voltage graphs for easier judgement.

## **BT1100 FEATURES:**

- · Battery, Cranking, and Charging System Tester
- 6V, 12V, and 12V Start-Stop Battery Test
- 12V & 24V Cranking/Charging System Test
- 6V/12V Internal Resistance Test
- TFT-LCD Display with Intuitive Graphical User Interface
- USB Type-C Wired Connection
- Supports DHC Result Management Software
- Update Firmware In-Field via PC Software
- Built-in 2" Thermal Printer & Customizable Facility Information
- Detachable/Replaceable 5.9' Cable
- Built-in Clamp and Cable Diagnostic Capability
- Strong and Durable Heavy-Duty Case Design
- Recall and Print Last 500 Test Results
- 12-Month Warranty



## BT1100 Specifications:

Operating Range: CCA: 25 to 3,000

Application: 6V/12V/12V Start-Stop

Battery Test, 12V/24V System Test, 6V/12V Internal Resistance Test

Voltage Range: 1V - 32V

Battery Types: Flooded, AGM Flat/Spiral,

EFB, VRLA, GEL, ODYSSEY

Battery Ratings: CCA/SAE, EN, EN2, IEC,

JIS, DIN, CA/MCA

Operating Temp: 0 - 50°C

(32 - 122°F)

Connection: USB Type-C